

Bulb Type	Base	Product #	Product Code	Description	Volts	Color Temp.	Lumens	CBCP	Life	Pkg. Qty.	Beam Spread	MOL
2 Watts												
MR11	G4	80603	MR11/2NW25/LED	Natural White	8-16	5000	80	470	40000	1/10	25°	1.39"
MR11	G4	80600	MR11/2WW25/LED	Warm White	8-16	2700	68	380	40000	1/10	25°	1.39"
MR11	G4	80604	MR11/2NW40/LED	Natural White	8-16	5000	80	140	40000	1/10	40°	1.39"
MR11	G4	80601	MR11/2WW40/LED	Warm White	8-16	2700	68	110	40000	1/10	40°	1.39"
MR11	G4	80605	MR11/2NW120/LED	Natural White	8-16	5000	80	40	40000	1/10	120°	1.39"
2.6 Watts												
⊕ R12	BA15s	80701	1383/3WW/LED	Warm White	12	2700	140	-	40000	1/10	-	2.52"
3 Watts												
MR16	G5.3	80609	MR16/3NW60/LED	Natural White	10-25	5000	140	-	40000	1/10	60°	2.10"
MR16	G5.3	80607	MR16/3WW60/LED	Warm White	10-25	2700	110	-	40000	1/10	60°	2.10"
5 Watts												
⊕ A16	Med.	80694	A16/5WW/LED	Warm White Dimmable	120	2700	220	-	40000	1/10	-	3.50"
MR16	G5.3	80619	MR16/5NW25/LED	Natural White	10-25	5000	180	350	40000	1/10	25°	2.00"
MR16	G5.3	80616	MR16/5WW25/LED	Warm White	10-25	2700	140	300	40000	1/10	25°	2.00"
⊕ MR16	G5.3	80673	MR16/M5NW25/LED	Natural White 3 LEDs	10-25	5000	220	600	40000	1/10	25°	2.16"
⊕ MR16	G5.3	80672	MR16/M5WW25/LED	Warm White 3 LEDs	10-25	2700	190	475	40000	1/10	25°	2.16"
MR16	G5.3	80620	MR16/5NW40/LED	Natural White	10-25	5000	180	275	40000	1/10	40°	2.00"
MR16	G5.3	80617	MR16/5WW40/LED	Warm White	10-25	2700	140	190	40000	1/10	40°	2.00"
MR16	G5.3	80614	MR16/M5NW40/LED	Natural White 3 LEDs	10-25	5000	220	450	40000	1/10	40°	2.00"
MR16	G5.3	80611	MR16/M5WW40/LED	Warm White 3 LEDs	10-25	2700	190	320	40000	1/10	40°	2.00"
MR16	G5.3	80625	MR16/5AMB40/LED	Amber	10-25	-	-	-	40000	1/10	40°	2.00"
MR16	G5.3	80623	MR16/5BLU40/LED	Blue	10-25	-	-	-	40000	1/10	40°	2.00"
MR16	G5.3	80624	MR16/5GRN40/LED	Green	10-25	-	-	-	40000	1/10	40°	2.00"
MR16	G5.3	80622	MR16/5RED40/LED	Red	10-25	-	-	-	40000	1/10	40°	2.00"
MR16	G5.3	80621	MR16/5NW120/LED	Natural White	10-25	5000	180	80	40000	1/10	120°	2.00"
MR16	G5.3	80618	MR16/5WW120/LED	Warm White	10-25	2700	140	60	40000	1/10	120°	2.00"
MR16	G5.3	80615	MR16/M5NW120/LED	Natural White 3 LEDs	10-25	5000	220	110	40000	1/10	120°	2.00"
MR16	G5.3	80612	MR16/M5WW120/LED	Warm White 3 LEDs	10-25	2700	190	90	40000	1/10	120°	2.00"
PAR16	Med.	80627	PAR16/5NW/FL/LED	Natural White	120	5000	180	1040	40000	1/10	40°	3.35"
PAR16	Med.	80626	PAR16/5WW/FL/LED	Warm White	120	2700	140	835	40000	1/10	40°	3.35"
PAR16	Med.	80631	PAR16/5AMB/FL/LED	Amber	120	-	-	-	40000	1/10	40°	3.35"
PAR16	Med.	80629	PAR16/5BLU/FL/LED	Blue	120	-	-	-	40000	1/10	40°	3.35"
PAR16	Med.	80630	PAR16/5GRN/FL/LED	Green	120	-	-	-	40000	1/10	40°	3.35"
PAR16	Med.	80628	PAR16/5RED/FL/LED	Red	120	-	-	-	40000	1/10	40°	3.35"
PAR36	MP Term	80652	PAR36/5WW/WFL/LED	Warm White	12	2700	240	-	40000	1/6	40°	2.75"
6 Watts												
⊕ MR16	G5.3	80688	MR16/5M6NW25/LED	Natural White 5 LEDs	10-25	5000	385	810	40000	1/10	25°	2.00"
⊕ MR16	G5.3	80689	MR16/5M6WW25/LED	Warm White 5 LEDs	10-25	2700	310	630	40000	1/10	25°	2.00"
MR16	G5.3	80658	MR16/5M6NW40/LED	Natural White 5 LEDs	10-25	5000	385	620	40000	1/10	40°	2.00"
⊕ MR16	G5.3	80657	MR16/5M6WW40/LED	Warm White 5 LEDs	10-25	2700	310	500	40000	1/10	40°	2.00"
⊕ PAR16	Med.	80698	PAR16/6NW/FL/LED2	Natural White Dimmable	120	5000	385	-	40000	1/10	40°	3.35"
⊕ PAR16	Med.	80697	PAR16/6WW/FL/LED2	Warm White Dimmable	120	2700	310	-	40000	1/10	40°	3.35"
8 Watts												
⊕ A19	Med.	80695	A19/8WW/LED	Warm White Dimmable	120	2700	360	-	40000	1/10	-	4.25"
⊕ PAR20	Med.	80700	PAR20/8NW/NFL/LED2	Natural White Dimmable	120	5000	520	-	40000	1/6	25°	3.50"
⊕ PAR20	Med.	80699	PAR20/8WW/NFL/LED2	Warm White Dimmable	120	2700	400	-	40000	1/6	25°	3.50"
PAR20	Med.	80636	PAR20/8NW/NFL/LED	Natural White	120	5000	320	-	40000	1/6	25°	3.50"
PAR20	Med.	80633	PAR20/8WW/NFL/LED	Warm White	120	2700	280	-	40000	1/6	25°	3.50"
PAR20	Med.	80638	PAR20/8RGB/NFL/LED	Color Changing Red, Green, Blue	120	-	-	-	40000	1/6	25°	3.50"
PAR20	Med.	80642	PAR20/8AMB/FL/LED	Amber	120	-	-	-	40000	1/6	40°	3.50"
PAR20	Med.	80640	PAR20/8BLU/FL/LED	Blue	120	-	-	-	40000	1/6	40°	3.50"
PAR20	Med.	80641	PAR20/8GRN/FL/LED	Green	120	-	-	-	40000	1/6	40°	3.50"
PAR20	Med.	80639	PAR20/8RED/FL/LED	Red	120	-	-	-	40000	1/6	40°	3.50"
PAR20	Med.	80635	PAR20/8NW/FL/LED	Natural White	120	5000	320	-	40000	1/6	40°	3.50"
PAR20	Med.	80632	PAR20/8WW/FL/LED	Warm White	120	2700	280	-	40000	1/6	40°	3.50"
PAR20	Med.	80637	PAR20/8NW/VWFL/LED	Natural White	120	5000	320	-	40000	1/6	120°	3.50"
PAR20	Med.	80634	PAR20/8WW/VWFL/LED	Warm White	120	2700	280	-	40000	1/6	120°	3.50"
9 Watts												
PAR36	MP Term	80651	PAR36/9WW/WFL/LED	Warm White	12	2700	500	-	40000	1/6	40°	2.75"
11 Watts												
⊕ PAR30	Med.	80683	PAR30/11NW/FL/LED	Natural White	120	5000	520	-	40000	6/24	40°	3.75"
⊕ PAR30	Med.	80682	PAR30/11WW/FL/LED	Warm White	120	2700	380	-	40000	6/24	40°	3.75"
13 Watts												
⊕ A22	Med.	80696	A22/13WW/LED	Warm White Dimmable	120	2700	520	-	40000	1/10	-	5.40"
14 Watts												
⊕ PAR30	Med.	80678	PAR30/14NW/SP/LED2	Natural White Dimmable	120	5000	920	-	40000	1/6	10°	4.61"
⊕ PAR30	Med.	80674	PAR30/14WW/SP/LED2	Warm White Dimmable	120	2700	740	-	40000	1/6	10°	4.61"
PAR30	Med.	80646	PAR30/14NW/NFL/LED	Natural White	120	5000	710	-	40000	1/6	25°	3.63"
PAR30	Med.	80643	PAR30/14WW/NFL/LED	Warm White	120	2700	590	-	40000	1/6	25°	3.63"
PAR30L	Med.	80653	PAR30L/14NW/NFL/LED	Natural White Long Neck	120	5000	710	-	40000	1/6	25°	4.75"

Bulb Type	Base	Product #	Product Code	Description	Volts	Color Temp.	Lumens	CBCP	Life	Pkg. Qty.	Beam Spread	MOL
14 Watts Cont'd												
PAR30L	Med.	80655	PAR30L/14WW/NFL/LED	Warm White Long Neck	120	2700	590	-	40000	1/6	25°	4.75"
⊛ PAR30	Med.	80679	PAR30/14NW/NFL/LED2/ND	Natural White Non-Dimmable	120	5500	1020	-	40000	1/6	30°	3.63"
⊛ PAR30	Med.	80675	PAR30/14WW/NFL/LED2/ND	Warm White Non-Dimmable	120	3100	740	-	40000	1/6	30°	3.63"
PAR30	Med.	80647	PAR30/14NW/FL/LED	Natural White	120	5000	710	-	40000	1/6	40°	3.63"
PAR30	Med.	80644	PAR30/14WW/FL/LED	Warm White	120	2700	590	-	40000	1/6	40°	3.63"
PAR30L	Med.	80654	PAR30L/14NW/FL/LED	Natural White Long Neck	120	5000	710	-	40000	1/6	40°	4.75"
PAR30L	Med.	80656	PAR30L/14WW/FL/LED	Warm White Long Neck	120	2700	590	-	40000	1/6	40°	4.75"
⊛ PAR30	Med.	80680	PAR30/14NW/FL/LED2	Natural White Dimmable	120	5000	920	-	40000	1/6	40°	4.61"
⊛ PAR30	Med.	80676	PAR30/14WW/FL/LED2	Warm White Dimmable	120	2700	740	-	40000	1/6	40°	4.61"
⊛ PAR30	Med.	80681	PAR30/14NW/WFL/LED2/ND	Natural White Non-Dimmable	120	5500	1020	-	40000	1/6	60°	3.63"
⊛ PAR30	Med.	80677	PAR30/14WW/WFL/LED2/ND	Warm White Non-Dimmable	120	3100	740	-	40000	1/6	60°	3.63"
PAR30	Med.	80648	PAR30/14NW/VWFL/LED	Natural White	120	5000	710	-	40000	1/6	120°	3.63"
PAR30	Med.	80645	PAR30/14WW/VWFL/LED	Warm White	120	2700	590	-	40000	1/6	120°	3.63"
18 Watts												
⊛ PAR38	Med.	80671	PAR38/18NW/FL/LED	Natural White Dimmable	120	5000	1240	-	40000	1/6	40°	4.81"
PAR38	Med.	80670	PAR38/18WW/FL/LED	Warm White Dimmable	120	2700	1020	-	40000	1/6	40°	4.81"
Remote												
		80649	PAR20/8RGB/REMOTE	Remote Control for PAR20 RGB								

⊛NEW ITEM!

* Useful Life is Defined as the point in time at which the lamp will maintain at least 70% of its initial lumens. The lamp will continue to burn past this point, but at decreased light levels.

Warranty - Commercial / Industrial: This product is warranted for 5 years from the date of purchase, based on 10 hours of use per day.

Warning: Due to multiple input voltage integrated circuits, this product is not compatible with dimming devices unless noted as dimmable.

Note: May not be compatible with all electronic transformers.

Not for use in enclosed fixtures.

Indoor use only.